

SPEC DATA

Product Type	Length (inch)	Width (inch)	Thickness (inch)	Coverage Per Piece	Weight Per Piece	Quantity Per Carton
Rock face panel	48	15 1/2	7/8 to 1 5/8	4.75 sq. ft.	5.1 lbs.	4
Ledger	48	4	2 1/2	.6 sq. ft.	2.9 lbs.	4
Sandstone Corner, Inside	48	3 1/2 each leg	2 5/8	2.00 sq. ft.	5.1 lbs.	2
Sandstone Corner, Outside	48	5 1/2 each leg	2 5/8	4.00 sq. ft.	6.0 lbs	2
Window/Door Trim	48	3 1/2	2 1/4	1.4 sq. ft.	2.5 lbs.	4
Outside Corner Cap	5 1/2	5 1/2	1 1/2	n/a	.4 lbs.	16
Inside Corner Cap	5 1/2	5 1/2	1 1/2	n/a	.4 lbs.	16
Starter Strip	48	2 1/4	26 ga.	n/a	.9 lbs.	40 (10/sleeve)
Large Mounting Blocks	10	13	2 1/4	n/a	1.75 lbs	1
Small Mounting Blocks	8	9	2 1/4	n/a	1 lbs	1
Sandstone Column Wraps/ Piece	36	6 1/2	1	n/a	1.5 lbs	4 pcs
Sandstone Column Wrap Cap	10 1/2	10 1/2	1 1/4	n/a	1.5 lbs	1
Sandstone Column Wrap 2 Pc Trim Kit	10 1/2 (assembled)	10 1/2 (assembled)	1 1/4	n/a	1.375 lbs	1
Flush Outside Corner	48"	3" (each side)	1 1/2"	2.0 sq. ft.	2.47	2
Ledger Outside Corner	9 1/2"(L) 7 3/4" (S)	4"	2 1/2"	10 1/4" Linear	.65 Lb.	2
Ledger Inside Corner	9 3/4" (L) 7 5/8" (S)	4"	2 1/2"	17 1/2" Linear	.67 lb.	2
Random Rock Outside Corner	7" X 11"	15 1/2"	1.5 "	1.7 sq. ft.	1.69 lbs	4
Accent Rocks, Large	11 1/2	15 1/2"	1.5"	1.2 sq. ft.	.94 lb.	3
Accent Rocks, Small	7	15 1/2"	1.5"	.63 sq. ft.	.71 lb.	3

SPEC DATA

Product type	Length (inch)	Width (inch)	Thickness (inch)	Coverage per piece	Weight per piece	Quantity per carton
Drystack Panel	47 3/4	5	7/8 to 1 1/2"	1.28 sq. ft.	1.3 lbs.	16
Ledgestone Panel	47 3/4	6 5/8	7/8 to 1 1/2"	1.78 sq. ft.	1.9 lbs.	12
Drystack Corner, Inside	40	4 3/4 each leg	1 1/2"	2.64 sq. ft.	2.42 lbs.	2
Drystack Corner, Outside	40	5 1/2 each leg	1 1/2"	3.23 sq. ft.	3.08 lbs.	2
Ledgestone Corner, Inside	40 1/2"	4 5/8 each leg	1 1/2"	2.67 sq. ft.	2.42 lbs.	2
Ledgestone Corner, Outside	40 1/2"	4 5/8 each leg	1 1/2"	2.67 sq. ft.	2.86 lbs.	2
Window/Door Trim	48	3 1/2	2 1/4	1.4 sq. ft.	2.5 lbs.	4
Starter Strip	48	2 1/4	26 ga.	n/a	.9 lbs.	40 (10/sleeve)
Ledger	48	4	2 1/2	.6 sq. ft.	2.9 lbs.	4
16" DS Column Wrap	36"	15 1/2"	1 3/4"	3.88 sq. ft.	3.52 lbs.	4
16" Col. Wrap Cap	17 1/2"	17 1/2"	1 1/2"	2.13 sq. ft.	2.64 lbs.	1
16" Col. Wrap Split Cap- 2 Pcs Per Set	17 1/2"	17 1/2"	1 1/2"	2.13 sq. ft.	2.64 lbs.	2pc / 1 set

Note: In all spec data information, weights and dimensions are approximate. Individual pieces may vary due to the manufacturing process.

Technical Data:

Flame Spread Factor, F9:	Heat Evolution Factor, Q:	Flame Spread Index, I8:	Ave Temp. Rise:
30.78	6.23	191.13	53.8 c

Color Fastness (per ANSI Z 124 xenon arc test): color change @ 200 hours: 0

Specific Gravity: .6

Insulation value: R 4.3 per inch of thickness

Hardness (durometer D): 68

Coefficient of Expansion (in. /in. F): 4.8"/in./C x 10(-5) (varies depending upon substrate attached to).

Fuel Contributed: 0

Flame Spread (per ASTM E162):

Installation:

Detailed installation instructions are available from your local distributor or on line at:

www.NextStone.com.

Maintenance:

NextStone products require minimal maintenance. Occasional rinsing with water is recommended. Prior to using any chemical products on NextStone, test a small inconspicuous area, verifying that no undesired side effects have occurred.

Warranty:

Warranty information is available from your local distributor or online at: www.NextStone.com.

Important:

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. Due to the inherent manufacturing characteristics of polyurethane, and the individual "hand" coloring of our product, dimensions and weights are approximate and the colors, as with natural stone, will vary.